

## Safety data sheet according SS 586 : Part 3

Date of issue: 27.05.2025

Version number 3

Revision: 27.05.2025

### \* 1 Identification

#### Product identifier

**Trade name: Cleaning spray type 1003**

**Relevant identified uses of the substance or mixture and uses advised against**

**Product category** PC35 Washing and cleaning products (including solvent based products)

#### Application of the substance / the mixture

Special cleaning agent for highly insulating parts such as plug connections and electronic components

#### Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Kistler Instrumente AG  
Eulachstrasse 22  
8408 Winterthur, Schweiz

##### Further information obtainable from:

+1 716 691 5100

Monday to Friday 7 am – 5 pm (EST)

**Emergency telephone number:** Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

### \* 2 Hazards identification

#### Classification of the substance or mixture



GHS02 flame

Aerosol 1      H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



GHS08 health hazard

Asp. Tox. 1      H304      May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411      Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2      H315      Causes skin irritation.

STOT SE 3      H336      May cause drowsiness or dizziness.

#### Label elements

**GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

**Hazard pictograms** GHS02, GHS07, GHS08, GHS09

**Signal word** Danger

(Contd. on page 2)

SG

# Safety data sheet

## according SS 586 : Part 3

Date of issue: 27.05.2025

Version number 3

Revision: 27.05.2025

(Contd. of page 1)

**Hazard-determining components of labelling:**

pentane  
cyclohexane

**Hazard statements**

Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

**Precautionary statements**

Use only outdoors or in a well-ventilated area.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

### \* 3 Composition/information on ingredients

**Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 109-66-0	pentane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	50-100%
CAS: 110-82-7	cyclohexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	15-20%
CAS: 106-97-8	butane, pure ⚠ Flam. Gas 1A, H220; ⚠ Press. Gas C, H280; ⚠ Acute Tox. 3, H331	10-15%
CAS: 74-98-6	propane ⚠ Flam. Gas 1A, H220; ⚠ Press. Gas C, H280	5-10%
CAS: 75-28-5	isobutane ⚠ Flam. Gas 1A, H220; ⚠ Press. Gas C, H280	1-5%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### \* 4 First-aid measures

**Description of first aid measures****General information:** Immediately remove any clothing soiled by the product.**After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

**After skin contact:**

Irritation. Repeated contact can lead to brittle or cracked skin.

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

## Safety data sheet according SS 586 : Part 3

Date of issue: 27.05.2025

Version number 3

Revision: 27.05.2025

(Contd. of page 2)

**After swallowing:**

If symptoms persist consult doctor.

Do not induce vomiting! Rinse mouth and drink plenty of water.

**Most important symptoms and effects, both acute and delayed** May cause drowsiness and dizziness**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

**Extinguishing media****Suitable extinguishing agents:**CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**Special hazards arising from the substance or mixture** Extremely flammable aerosol**Advice for firefighters****Protective equipment:**

Use self-contained breathing apparatus. Wear protective clothing to prevent eye or skin contact.

### 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

**Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.**Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool and well-ventilated place. Keep away from sources of ignition. Keep away from direct sunlight. Ensure that lighting and electrical equipment are not sources of ignition.

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:** Keep container tightly sealed.**Specific end use(s)** No further relevant information available.

### \* 8 Exposure controls/personal protection

**Control parameters****Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

— SG —

## Safety data sheet according SS 586 : Part 3

Date of issue: 27.05.2025

Version number 3

Revision: 27.05.2025

(Contd. of page 3)

**Additional information:** The lists valid during the making were used as basis.

### Exposure controls

**Appropriate engineering controls** No further data; see section 7.

### Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### Respiratory protection:

Respiratory protection recommended when the TLV limit is exceeded .

If ventilation is inadequate, wear a respirator. Suitable respiratory protection: Filter type A for organic gases and vapors.

#### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

Butyl rubber, BR

**For the permanent contact gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

Butyl rubber, BR

Nitrile rubber, NBR

**Not suitable are gloves made of the following materials:** PVC gloves

**Eye protection:** Not required.

**Body protection:** Protective work clothing

## \* 9 Physical and chemical properties

### Information on basic physical and chemical properties

#### General Information

Physical state	Aerosol
Colour:	Opaque
Odour:	Solvent-like
pH-value:	Mixture is a gas.
Initial boiling point and boiling range:	Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Evaporation rate	Not applicable.
Flammability	Not applicable.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	9.5 Vol %
Vapour pressure at 20 °C:	8300 hPa
Vapour pressure:	
Vapour density	Not determined.

(Contd. on page 5)

## Safety data sheet according SS 586 : Part 3

Date of issue: 27.05.2025

Version number 3

Revision: 27.05.2025

(Contd. of page 4)

<b>Density:</b>	Not determined.
<b>Relative density</b>	Not determined.
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Particle characteristics</b>	Not applicable.
<b>Other information</b>	
<b>Appearance:</b>	
<b>Form:</b>	Aerosol
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Ignition temperature:</b>	Product is not selfigniting.
<b>Explosive properties:</b>	Pressurised container: May burst when heated.
<b>Solvent content:</b>	
<b>VOC (EC)</b>	100.00 %

### 10 Stability and reactivity

**Reactivity** Extremely flammable aerosol. Pressurised container: May burst if heated.

**Chemical stability** The product is stable under normal conditions.

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

**Conditions to avoid**

Avoid contact with hot surfaces. Heat. No naked flames, no sparks. Remove all sources of ignition.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

**Information on toxicological effects**

**Acute toxicity**

**LD/LC50 values relevant for classification:**

**CAS: 110-82-7 cyclohexane**

Oral	LD50	12705 mg/kg (rat)
------	------	-------------------

**CAS: 106-97-8 butane, pure**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**Primary irritant effect:**

**Skin corrosion/irritation** Irritant to skin and mucous membranes.

**Serious eye damage/irritation** No irritating effect.

**Respiratory or skin sensitisation** No sensitising effects known.

**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** No CMR effects known.

### 12 Ecological information

**Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability** No further relevant information available.

**Bioaccumulative potential** No further relevant information available.

(Contd. on page 6)

SG

Revision: 27.05.2025

Toxic for aquatic organisms

**Recommendation:** Disposal must be made according to official regulations.

## 2.1

SG

## Safety data sheet

### according SS 586 : Part 3

Date of issue: 27.05.2025

Version number 3

Revision: 27.05.2025

(Contd. of page 6)

<b>Packing group</b> <b>ADR, IMDG, IATA</b>	Void
<b>Environmental hazards:</b>	Product contains environmentally hazardous substances: cyclohexane
<b>Marine pollutant:</b>	No
<b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR</b> <b>Limited quantities (LQ)</b> <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
<b>Transport category</b> <b>Tunnel restriction code</b>	2 D
<b>IMDG</b> <b>Limited quantities (LQ)</b> <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
<b>Special precautions for user</b> <b>Hazard identification number (Kemler code):</b> <b>EMS Number:</b> <b>Stowage Code</b>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
<b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
<b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.2, ENVIRONMENTALLY HAZARDOUS

## \* 15 Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

**GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

**Hazard pictograms** GHS02, GHS07, GHS08, GHS09

**Signal word** Danger

### Hazard-determining components of labelling:

pentane

cyclohexane

### Hazard statements

Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

(Contd. on page 8)

SG

## Safety data sheet according SS 586 : Part 3

Date of issue: 27.05.2025

Version number 3

Revision: 27.05.2025

(Contd. of page 7)

**Precautionary statements**

Use only outdoors or in a well-ventilated area.  
 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 Specific treatment (see on this label).  
 Do NOT induce vomiting.  
 Take off contaminated clothing and wash it before reuse.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

The information corresponds to the current state of knowledge. Kistler reserves the right to make technical changes. Liability for consequential damage resulting from the use of Kistler products is excluded.

©2025 Kistler Group, Eulachstrasse 22, 8408 Winterthur, Switzerland

Phone +41 52 224 11 11, Fax +41 52 224 14 14, info@kistler.com, www.kistler.com

Kistler is a registered trademark of Kistler Holding AG.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H220 Extremely flammable gas.  
 H225 Highly flammable liquid and vapour.  
 H280 Contains gas under pressure; may explode if heated.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H331 Toxic if inhaled.  
 H336 May cause drowsiness or dizziness.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

**\* Data compared to the previous version altered.**