

Page 1/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Grouting compound type 1000A1 Comp. A, resin

Article number: 1000A1 Komp. A UFI: HM00-Q0KV-900F-FEME

1.2 Relevant identified uses of the substance or mixture and uses advised against Potting resin for sensors

Application of the substance / the mixture Auxiliary

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Kistler Instrumente AG Eulachstrasse 22 8408 Winterthur, Schweiz

Further information obtainable from:

+1 716 691 5100

Monday to Friday 7 am - 5 pm (EST)

1.4 Emergency telephone number: +49 (0)6132-84463 (24 h; GBK GmbH)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms GHS07, GHS09

Signal word Warning

Hazard-determining components of labelling:

formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol bis[4-(2,3-epoxypropoxy)phenyl]propane

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

Trade name: Grouting compound type 1000A1 Comp. A, resin

(Contd. of page 1)

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

| Dangerous components: | | | | |
|-----------------------|---|--------|--|--|
| CAS: 9003-36-5 | formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | 70-90% | | |
| | 4 Aquatic Chronic 2, H411; 🕩 Skin Irrit. 2, H315; Skin Sens. 1, H317 | | | |
| CAS: 1675-54-3 | bis[4-(2,3-epoxypropoxy)phenyl]propane | 15-30% | | |
| EINECS: 216-823-5 | ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % | | | |

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

If symptoms persist consult doctor.

Do not induce vomiting! Rinse mouth and drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

Trade name: Grouting compound type 1000A1 Comp. A, resin

(Contd. of page 2)

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection when fumes/aerosols appear.

Avoid contact with skin and eyes.

Wear protective clothing.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

| DNELs | | | | |
|---|-----------------------------------|---------------------------------|--|--|
| CAS: 9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | | | | |
| Oral | DNEL (long-term systemic effects) | 6.25 mg/kg/day (General public) | | |
| Dermal | DNEL (long-term systemic effects) | 62.5 mg/kg/day (General public) | | |
| | | 104.15 mg/kg/day (Worker) | | |
| Inhalative | DNEL (long-term systemic effects) | 8.7 mg/m3 (General public) | | |
| | | 29.39 mg/m3 (Worker) | | |
| | | (Contd. on page | | |

(Contd. on page

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

Trade name: Grouting compound type 1000A1 Comp. A, resin

(Contd. of page 3)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Butyl rubber, BR

Eye/face protection



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state
Colour:
Yellowish
Odour:
Odour threshold:
Melting point/freezing point:
Boiling point or initial boiling point and boiling range
>200 °C
Flammability
Liquid
Yellowish
Odourless
Odourless
Not determined.
Undetermined.
Not applicable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:>200 °CDecomposition temperature:Not determined.

pH Mixture is non-soluble (in water).

(Contd. on page 5)

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

Trade name: Grouting compound type 1000A1 Comp. A, resin

(Contd. of page 4)

Viscosity:

Kinematic viscosity at 20 °C 5400-6700 mm2/s (DIN 53211/4)

Not determined. Dynamic:

Solubility

water: Insoluble.

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 1.2 g/cm3 Relative density Not determined. Not determined. Vapour density

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: In general, product does not present an explosion hazard.

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void Flammable gases Void Void **Aerosols** Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void **Pyrophoric solids** Void

Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

Trade name: Grouting compound type 1000A1 Comp. A, resin

(Contd. of page 5)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

| LD/LC5 | LD/LC50 values relevant for classification: | | | | |
|---------|---|-------------------|--|--|--|
| CAS: 90 | CAS: 9003-36-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | | | | |
| Oral | LD50 | >5000 mg/kg (rat) | | | |
| Dermal | LD50 | >2000 mg/kg (rat) | | | |
| CAS: 16 | CAS: 1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane | | | | |
| Oral | LD50 | 19800 mg/kg (rat) | | | |
| Dermal | LD50 | >2000 mg/kg (rat) | | | |

Primary irritant effect:

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) No CMR effects known.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Toxic for fish

Other information: Do not discharge into drains, surface waters or groundwater.

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- IE

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

Trade name: Grouting compound type 1000A1 Comp. A, resin

(Contd. of page 6)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

| SECTION 14: Transport information | | |
|--|---|--|
| 14.1 UN number or ID number ADR, IMDG, IATA | UN3082 | |
| 14.2 UN proper shipping name ADR IMDG, IATA | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (formaldehyde, oligomeric reaction products w 1-chloro-2,3-epoxypropane and phenol) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI N.O.S. (formaldehyde, oligomeric reaction products with chloro-2,3-epoxypropane and phenol) | |
| 14.3 Transport hazard class(es) | | |
| ADR, IMDG | | |
| | | |
| Class Label | 9 9 | |
| IATA | | |
| 1 1 2 2 2 3 3 3 3 3 3 3 3 3 3 | | |
| Class | 9 | |
| Label | 9 | |
| 14.4 Packing group ADR, IMDG, IATA | III | |
| 14.5 Environmental hazards: Marine pollutant: Special marking (IATA): | No Symbol (fish and tree) | |
| 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category | Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A | |
| 14.7 Maritime transport in bulk according to IM instruments | Not applicable. | |

(Contd. on page 8)

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

Trade name: Grouting compound type 1000A1 Comp. A, resin

(Contd. of page 7)

| Transport/Additional information: | |
|-----------------------------------|---|
| ADR | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| Transport category | 3 |
| Tunnel restriction code | (-) |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| , | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation": | UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, |
| G | LIQUID, N.O.S. (FORMALDEHYDE, OLIGOMERIC REACTION |
| | PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND |
| | PHENOL), 9, III |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The information corresponds to the current state of knowledge. Kistler reserves the right to make technical changes. Liability for consequential damage resulting from the use of Kistler products is excluded. ©2025 Kistler Group, Eulachstrasse 22, 8408 Winterthur, Switzerland

(Contd. on page 9)

Printing date 05.06.2025 Version number 1 Revision: 05.06.2025

Trade name: Grouting compound type 1000A1 Comp. A, resin

(Contd. of page 8)

Phone +41 52 224 11 11, Fax +41 52 224 14 14, info@kistler.com, www.kistler.com

Kistler is a registered trademark of Kistler Holding AG.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (RÈACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

IE -