

RoaDyn S660

Type 9248A1

Wheel force transducer for racing, SUVs, transporters and light trucks

Wheel Force Transducers for electric vehicles (EVs), vehicles with new powertrain concepts (NEVs) and traditional internal combustion engines to measure three forces and three moments on a rotating wheel; a major constituent in modern vehicle development.

- Best signal-to-noise ratio: digitization in the sensor
- Highest accuracy: vanishing crosstalk and modulation with best-in-class hexapod calibration
- Flexible data transmission: swappable inboard / outboard and wireless transmission
- Approved high quality due to durability test according to SAE J328
- User-friendly thanks to modular design

Description

The RoaDyn wheel force transducers (WFT) is a multiaxial measuring system for automotive development and testing. A RoaDyn WFT replaces a standard wheel for the measurement of three forces (F_x , F_y , F_z) and three moments (M_x , M_y , M_z) applied through the tire contact patch.

Due to the modular design of the RoaDyn WFTs, they can be adapted to most vehicles on the market.

Suitable mechanical components like inner part, outer part and wheel offset adapter are used to mount the replaceable 3-component load cells between wheel hub and rim ring. This modularity offers an extremely high degree of versatility. All of the standard components of the system apart from the mechanical elements can be retained when it is adapted to suit different rim sizes and wheel hub geometries.

Application

- Road load data acquisition (RLDA) as needed e.g. for vehicle durability or vehicle dynamics
- Tire testing
- Noise Vibration Harshness (NVH)
- Development of vehicle dynamics control systems (ABS, ESP, ...)
- Advanced driver assistance systems (ADAS testing)

The Kistler RoaDyn WFTs are adaptable to the spinning application on vehicles driving on the road as well as on test rig, as eg. axle test rigs or driving simulators, when the wheel is not rotating.



The Kistler RoaDyn S6 Wheel Force Transducer is a high sophisticated, modular and flexible measuring unit. Thus, it is adaptable to diverse applications even if they are not stated in this document.

Signal processing

The signals are amplified before leaving the load cells and passed on to the hub electronics for filtering, digitization and encoding. The data stream is transmitted contact-free via in-, out-board or wireless transmission to the on-board electronics. Here the physical quantities F_x , F_y , F_z , M_x , M_y and M_z are calculated from the raw signals and transformed from the rotating coordinate system of the wheel into the non-rotating vehicle coordinate system. The measurement data is output in both analog and digital form. Amongst others, CAN and Ethernet are available as digital output format.

Page 1/5

This information corresponds to the current state of knowledge. Kistler reserves the right to make technical changes. Liability for consequential damage resulting from the use of Kistler products is excluded.

^{© 2011... 2024} Kistler Group, Eulachstrasse 22, 8408 Winterthur, Switzerland Tel. +41 52 224 11 11, info@kistler.com, www.kistler.com. Kistler is a registered trademark of Kistler Holding AG. Kistler Group products are protected by various intellectual property rights. For more details visit www.kistler.com.

RoaDyn S660 – Wheel force transducer for racing, SUVs, transporters and light trucks, Type 9248A1 $\,$

KISTLER

measure. analyze. innovate.

Calibration

Each RoaDyn WFT is calibrated on two levels: First each individual loadcell is calibrated. Second, the entire sensor is calibrated using an advanced and unique calibration procedure on a hexapode. These leads to a 6x6 compensation matrix, which is used to improve the accuracy by taking the sensitivity of the sensor system into account. Due to this approach, the single loadcells can be exchanged without the need for a calibration of the whole system again and the sensor shows a vanishing modulation.



Technical data

Measuring range 1)			
F _x / F _z	kN	60	
Fy	kN	36	
M _{x/} M _z	kN∙m	7.5	
My	kN∙m	8.5	
Angle resolution	0	≈0.1	
Measurment uncertainty 2)			
Linearity	%FS	≤0.5	
Typical	%FS	≤0.15	
Hysteresis	%FS	≤0.5	
Typical	%FS	≤0.15	
Crosstalk forces	%FS	≤0.5	
Typical	%FS	≤0.1	
Other technical data			
Max speed 3)	km/h	>300	
Shock resistance	g	50	
Degree of protection	IP	IP65	
Operating temperature range	°C	< 125	
Fatigue load rating	The requirements		
	according to SAE J328 are exceeded.		
Minimal rim size	inch	15	
Sensor weight 4)	kg	15	

¹⁾ It is assumed that these extreme values do not occur simultaneously. The moments refer to the wheel center.

²⁾ The typical accuracy corresponds to the median of the results of end-of line and recalibrations.

³⁾ Vehicle Speed depending on the wheel diameter.

⁴⁾ With adaptation without rim, the real weight depends on the specific geometry of the sensor assembly.

This information corresponds to the current state of knowledge. Kistler reserves the right to make technical changes. Liability for consequential damage resulting from the use of Kistler products is excluded.

© 2011... 2024 Kistler Group, Eulachstrasse 22, 8408 Winterthur, Switzerland Tel. +41 52 224 11 11, info@kistler.com, www.kistler.com. Kistler is a registered trademark of Kistler Holding AG. Kistler Group products are protected by various intellectual property rights. For more details visit www.kistler.com.

Page 2/5



Sensor setup



Fig.1: Structure/components of the RoaDyn S660 WFT for standard applications with in-board transmission

Page 3/5

This information corresponds to the current state of knowledge. Kistler reserves the right to make technical changes. Liability for consequential damage resulting from the use of Kistler products is excluded.

© 2011... 2024 Kistler Group, Eulachstrasse 22, 8408 Winterthur, Switzerland Tel. +41 52 224 11 11, info@kistler.com, www.kistler.com. Kistler is a registered trademark of Kistler Holding AG. Kistler Group products are protected by various intellectual property rights. For more details visit www.kistler.com.



RoaDyn S660 measuring chain configurations

Wheel force transducer	Data transmission	Connecting cable	On-board	electronics
Type 9248A1 with wheel electronics Type 5241A2 and rim Type Z39913A	Type 5240A, 5242A In-board transmission unit consisting of rotor and stator	Type Z30430A Connection between stator and on-board electronics	Type 9817B KiRoad Performance	Type 18025602 KiCenter
				A CONTRACT OF A
Wheel force transducer	Data transmission	Connecting cable	On-board	electronics
Type 9248A1 with wheel electronics Type 5241A2 and rim Type Z39913A	Type 5248A Out-board transmission unit	Type Z30430A Connection between stator and on-board electronics	Type 9817B KiRoad Performance	Type 18025602 KiCenter
0000				

Wireless

Wheel force transducer	Data transmission	On-board electronics		
Туре 9279А1	Type 9822A Wheel unit	Type 9813C KiRoad Wireless HDR	Type 18025602 KiCenter	
			A REAL PROPERTY OF A REAL PROPER	

Page 4/5

This information corresponds to the current state of knowledge. Kistler reserves the right to make technical changes. Liability for consequential damage resulting from the use of Kistler products is excluded.

© 2011... 2024 Kistler Group, Eulachstrasse 22, 8408 Winterthur, Switzerland Tel. +41 52 224 11 11, info@kistler.com, www.kistler.com. Kistler is a registered trademark of Kistler Holding AG. Kistler Group products are protected by various intellectual property rights. For more details visit www.kistler.com.

KISTLER

measure. analyze. innovate.

Mounting the in-board transmission

The wireless inboard transmission unit is mounted on the inside of the rim and is thus protected against contact with obstacles. In the case of inboard transmission, a suitable mounting device for the stator is mounted on the wheel carrier or suspension strut. An adjustment gauge is then used to determine the position of the stator and the position of the mounting bracket.

Mounting the out-bord transmission

The outboard transmission is mounted together with the torque support on the outside of the wheel.

For outboard transmission, the vehicle setup needs to be extended with an additional support arm to which the on-board electronics cable is fixed.

Data Analysis with jBEAM Durability

jBEAM is an analysis and visualization software that works independently of operating system as a standalone program. Full interactivity and performance allow for quick analysis, visualization and evaluation of measurement data. The jBEAM Durability Edition continues all the key components for the optimal evaluation of load data and supports the user during vehicle and component validation at the test stand.

		- ·· · ·	
Included accessories	Type/Art. no.	Optional accessories	Type/Art. no.
 6x load cells (strain gauge basis) 	9190A8D7	CFRP rim	9709A
• Outer part	9731A6	 Precision spirit level 	Z30208
• Inner part	9729A6	 Adjusting gauge for stator mounting 	Z39911Q
• Rim	Z39913A	Tire mounting	Z30210
• Offset adapter	9713A	3-channel strain gauge	
Hub adapter package Al	9711A3	bridge amplifier (SGAM)	2237A1
		3-channel thermocouple	
Signal transmission / electronics:		amplifier (TCAM)	2237A2
KiRoad Performance	9817B		
Wheel electronic	5241A		
 In-board transmission 	5240A,	Ordering code	
including stator and rotor	5242A	• RoaDyn S660	
Out-board transmission	5248A	Wheel force transducer for racing,	
• Extension cable	Z30430A	SUVs, transporters and light trucks	Тур 9248А1
• KiRoad Wireless HDR	9813C		
• Wheel Unit	9822A		
Battery with charger for Wheel Unit			
Rotary encoder	5262A		

This information corresponds to the current state of knowledge. Kistler reserves the right to make technical changes. Liability for consequential damage resulting from the use of Kistler products is excluded.

© 2011... 2024 Kistler Group, Eulachstrasse 22, 8408 Winterthur, Switzerland Tel. +41 52 224 11 11, info@kistler.com, www.kistler.com. Kistler is a registered trademark of Kistler Holding AG. Kistler Group products are protected by various intellectual property rights. For more details visit www.kistler.com.

Page 5/5