

## Valves

### Types

1715/1720/1725/1750...

#### Type 1715 long

Maximal Working Pressure 250 Bar

- Divided spindle
- $\frac{3}{4}$ " connection for SKL engine
- Option with thread cup
- Height: 148 mm



#### Type 1720/S

Maximal Working Pressure 250 Bar

- Shifted corner valve
- Divided spindle
- Hexagon handle 17 mm
- Mounting thread M24x1,5
- Option with thread cup



#### Type 1715

Maximal Working Pressure 250 Bar

- With divided spindle
- All connection thread customer wish
- Option with thread cup
- Height: 128 mm
- Angle: 45°



#### Type 1725

Maximal Working Pressure 250 Bar

- All connection thread customer wish
- Option with thread cup
- Height: 110 mm



#### Type 1715/1

Maximal Working Pressure 250 Bar

- Swinging, divided spindle
- All connection thread customer wish
- Option with thread cup
- Height: 128 mm
- Angle: 45°



#### Type 1750

Maximal Working Pressure 300 Bar

- Discharge pressure 300 bar
- Other versions on request



#### Type 1720

Maximal Working Pressure 250 Bar

- Divided spindle
- Corner valve
- All connection thread customer wish
- Option with thread cup
- Height: 116 mm



All valves Made in Germany!